# 6\*9cm

# 温湿度计用户手册

### 一、产品图解



## 操作方法



### 三、产品规格

温度測量范围: -50℃~+70℃ (-58°F~+158°F) 温度測量精度: ±1℃ (1.8°F)

温度測量精度: ±1℃ (1.8℃ 温度分辨率: 0.1℃ (0.2℃)

温度分析学: 0.10 (0.21) 湿度测量范围: 10%RH-99%RH

湿度测量精度: ±5%RH 湿度分辨率: 1%

使用电池: CR2032\*1

### 四、基本功能

开关机功能

单位转换

温度显示

湿度显示

他反业小 舒适度标识

## 五、舒适度标识说明

湿度显示10%-39%之间, 屏幕显示 ②: 湿度显示40%-70%之间, 屏幕显示 ③: 湿度显示71%-99%之间, 屏幕显示 ③:

# 6\*9cm

# User manual of Thermo-hygrometer

## ◆Product diagram



#### ◆Operation Method



- 1. In the power-off state, short press the key to turn on;
- 2. In the power-on state, short press the key to switch the temperature unit to °C (Celsius) °F (Fahrenheit);

  3. In the power-on state, press and hold the key for 3

### ◆ Product specifications

Temperature measurement range: -50°C ~+70°C (-58°F ~+158°F)

seconds to power off.

Temperature measurement accuracy: ±1 °C (1.8°F)

Temperature resolution: 0.1 °C (0.2 °F)

Humidity measurement range: 10%RH-99%RH

Humidity measurement accuracy: ±5%RH

Humidity resolution: 1%

Power supply: CR2032\*1

#### ◆Basic functions

Power on/off function °C/°F switch diaplay

temperature display

Humidity display

### Description of comfort level

Humidity display between 10%-39% : (2);

Humidity display between 40%-70%: ; ; Humidity display between 71%-99%; . . .